

/ Descriptions

1000V 1A SOD-123FL
Surface Mount General Purpose Silicon Rectifiers Reverse Voltage 1000V Forward Current 1A
SOD-123FL thin package.

/ Features

RoHS 2011/65/EU AEC-Q101

Glass Passivated Chip Junction Ideal for automated placement Lead free in comply with EU RoHS
2011/65/EU directives For surface mounted applications, Qualified to AEC-Q101 Standards for High
Reliability, HF Product.


/ Applications

General purpose, Meet the stringent requirements of automotive applications.

/ Equivalent Circuit




/ Pinning



PIN	DESCRIPTION
1	Cathode
2	Anode

The recommended mounting pad size



/ Marking

See Marking Instructions.

Parameter	Symbol	Rating	Unit
		BR1N4007WQ	
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	1000	V
Maximum RMS Voltage	V_{RMS}	700	V
Maximum DC Blocking Voltage	V_{DC}	1000	V
Maximum Average Forward Rectified Current @ Fig.1	$I_{F\ AV}$	1	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I_{FSM}	30	A
Peak Forward Surge Current 1.0 ms Single Half Sine Wave Superimposed on Rated Load	I_{FSM}	60	A

/ Electrical Characteristic Curve

Fig.1 Forward Current Derating Curve




Fig.2 Typical Reverse Characteristics




Fig.3 Typical Forward Characteristics




Fig.4 Typical Junction Capacitance






Fig.5 Maximum Non-Repetitive Peak Forward Surge Current



/ Package Dimensions

SOD-123FL



/ Marking Instructions




S1M

Note:

S1M Product Type Code

**** Lot No. Code, code change with Lot No

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|----|-----------|---|
| 1 | 150 | 200 | 60 | 120sec; | 1.Preheating:150~200 , Time:60~120sec. |
| 2 | 255±5 | | | 5±0.5sec; | 2.Peak Temp.:255±5 , Duration:5±0.5sec. |
| 3 | | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOD-123FL	3,000	8	24,000	6	144,000	7 ×8	185×180×105	390×385×205

/ Notices