

BRCL4058NZZ

1A

/

BRCL4058NZZ

P-MOSFET

4.2V

4.2V

1/10

BRCL4058NZZ

6.8V OVP

VDD

36V

0V

1A


/ /


2.8V

DFN2×2-8L

RoHS

USB





1	TEMP	
2	PROG	
3	GND	
4	VDD	5V
5	BAT	
6	STDBY	
7	CHRG	
8	CE	

VDD/CHRG/STDBY Pin Voltage	$V_{VDD/CHRG/STDBY}$	-0.3~36	V
VCE Pin Voltage	V_{CE}	-0.3~32	
BAT Pin Voltage	V_{BAT}	-5~15	
PROG Pin Voltage	V_{PROG}	-0.3~6	
TEMP Pin Voltage	V_{TEMP}	-0.3~15	
Operating Ambient Temperature Range	T_{OP}	-40~+85	°C
Storage Temperature	T_{stg}	-55~+150	°C
Lead Temperature (Soldering, 10s)	T_{solder}	260	°C
ESD	HBM	2000	V
	MM	200	V

Rev.B Aug.-2025



D

CHRG Pin Output Current	I _{CHRG}	V _{DD} =5V;V _{CHRG} =1V	1	2.5	I 5	mA

36.8

BRCL4058NZZ

/

BRCL4058NZZ

USB

AC

1A

,

36V

6.8V

VDD

UVLO

PROG

1%

BAT

2.8V,

1/10

BAT

2.8V

BAT

BRCL4058NZZ

1/10

$I_{CH}=1000/R_{PROG}$

I_{CH}

R_{PROG}

R_{PROG}

200mA

$R_{PROG}=1000/0.2=5K\Omega$

R_{PROG}

1%

R_{PROG}

$R_{PROG}(K\Omega)$	$I_{CH}(mA)$
1	1000
1.2	830
1.5	666
5	200

BAT

BRCL4058NZZ

2ms

$T_{RECHARGE}$

4.05V

80

90

140

BRCL4058NZZ

UVLO

VDD

VDD

VDD

200mV

BRCL4058NZZ

VDD

VDD

BRCL4058NZZ

CHRG

STDBY


CHRG

STDBY

	CHRG/	STDBY/
(TEMP)		
VDD		

DFN2 x2-8L-0.75

Unit:mm




Rev.00 202012



4058N
XX

BRCL4058NZZ-4.2	4058N-42/****

b r n o d o f b l f b i f i a b f d d b



Note:

- 1

150 180

60 90sec;

1.Preheating:150~180 , Time:60~90sec.
- 2

245±5

5±0.5sec;

2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3

2 10 /sec.

3. Cooling Speed: 2~10 /sec.

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
DFN2×2-8L	4,000	10	40,000	4	160,000	7 ×8	210×205×205	445×435×230

All information provided in this document is subject to legal disclaimers.