



/ Revised record

A	2022-7-18	ALL	ALL		

/ Descriptions

SOT-89

Low dropout linear regulator in a SOT-89 Plastic Package .

/ Features

20V

1.5 μ A


$\pm 2\%$

Low power consumption,Low voltage drop,Small temperature drift coefficient,High input voltage up to 20V,The static current 1.5 μ A,The output voltage accuracy: $\pm 2\%$,HF Product.



/ Applications

For use in power equipment,Communication equipment,Audio and video equipment.

/ Equivalent Circuit



/ Pinning



PIN1 GND

PIN 2 VIN

PIN 3 VOUT

/ Marking

/ See Marking Instructions.




Parameter	Symbol	Rating	Unit
Working Voltage	V_{IN}	-0.3~+20	V
Thermal Resistance	$R_{\theta JA}$	200	/W
Power Consumption	P_W	500	mW
Storage Temperature	T_{STG}	-50~+125	
Working Temperature	T_A	-40~+85	

Notes: If the device operating conditions over the maximum rating of the above-mentioned conditions, may cause permanent damage to the device. The above parameters is only part of the operating conditions the maximum, we do not recommend the device running outside the scope of this specification. If the device to work long hours under the condition of absolute maximum limit, its stability may be affected.

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
-----------	--------	-----------------	-----	-----	-----	------

/ Typical Application Circuit


/ Basic Application



/ High Output Current Voltage Regulator




/ Short-Circuit Protection




/ Typical Application Circuit


/ Circuit for Increasing Output Voltage



/ Constant Current Regulator




/ Double Output Circuit



/ Package Dimensions

SQT-89


单位: mm



Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters	
	Min	Max		Min	Max
A	4.4	4.7	a1	0.36	0.56
B	2.25	2.65		0.36	0.56



/ Marking Instructions



说明：

7333： 为型号代码

**： 为生产批号代码，随生产批号变化


Note:

7333: Product Type

**： Lot No. Code, code change with Lot No



() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|----|-----------|--|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180°C, Time:60~90sec. |
| 2 | 245±5 | | | 5±0.5sec; | 2.Peak Temp.:245±5°C, Duration:5±0.5sec. |
| 3 | | | 2 | 10°C/sec. | 3. Cooling Speed: 2~10°C/sec. |

/ Resistance to Soldering Heat Test Conditions

260±5°C

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box	Outer Box
SOT-89	1,000	7	7,000	6	42,000	7" ×12	180×120×180	390×385×205

/ Notices