

/ Descriptions

40V 5.0A SMB

Surface Mount Schottky Barrier Rectifiers, Reverse Voltage 40V,Forward Current: 5.0A ,SMB package.

/ Features

Low power loss, High efficiency, High forward surge current capability, For surface mounted applications. HF product.


/ Applications

General purpose.

/ Equivalent Circuit




/ Pinning



PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode

The recommended mounting pad size



/ Marking

Type number	Marking
SSL54B	SSL54

/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	40	V
Maximum RMS voltage	V_{RMS}	28	V
Maximum DC Blocking Voltage	V_{DC}	40	V
Maximum Average Forward Rectified Current	$I_F (AV)$	5	A
Peak Forward Surge Current 8.3 ms Single Half Sine Wave Superimposed on Rated Load	I_{FSM}	150	A
Typical Junction Capacitance ¹	C_j	800	pF
Typical Thermal Resistance ²	$R_{\theta JA}$	45	°C/W
Operating Junction Temperature Range	T_j	-55~+150	°C
Storage Temperature Range	T_{stg}	-55~+150	°C


Note:

- 1 Measured at 1 MHz and applied reverse voltage of 4 V D.C
- 2 P.C.B. mounted with 2.0" X 2.0" (5 X 5 cm) copper pad areas.

/ Electrical Characteristics(Ta=25)


Parameter	Symbol	Test Conditions	数值 Rating	Unit
Maximum Instantaneous Forward Voltage	V_F	$I_F=5.0A$	0.45	V
Maximum DC Reverse Current at Rated DC Blocking Voltage	I_R	$T_a=25^{\circ}C$ $T_a=100^{\circ}C$	1 50	mA

/ Electrical Characteristic Curve




/ Package Dimensions

SMB



/ Marking Instructions



SSL54

1 *


3 *

Note:

SSL54 Product Type Code

**** Lot No. Code The 1st * means:YM Code The last 3 * means:little Lot No
Code

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|--------|---|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | | 5±0.5sec; | | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SMB	3000	5	15000	5	75000	7" ×11	185X180X105	390X385X205

/ Notices