

TIP117

Rev. H Oct.-2018

/ Descriptions

Silicon PNP transistor in a TO-220 Plastic Package.


/ Features

Complement to TIP112.


/ Applications

Medium power linear switching applications.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter

/ h_{FE} Classifications & Marking

See Marking Instructions.


/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-100	V
Collector to Emitter Voltage	V_{CEO}	-100	V
Emitter to Base Voltage	V_{EBO}	-5.0	V
Collector Current - Continuous	I_C	-2.0	A
Peak Collector Current	I_{CP}	-4.0	A
Base Current - Continuous	I_B	-50	mA
Collector Power Dissipation	$P_C(T_C=25)$	50	W
Junction Temperature	T_j	150	
Storage Temperature Range	T_{stg}	-55 150	

/ Electrical Characteristics(Ta=25)


Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C=-30mA$ $I_B=0$	-100			V
Collector Cut-Off Current	I_{CEO}	$V_{CE}=-50V$ $I_B=0$			-2.0	mA
Collector Cut-Off Current	I_{CBO}	$V_{CB}=-100V$ $I_E=0$			-1.0	mA
Emitter Cut-Off Current	I_{EBO}	$V_{EB}=-5V$ $I_C=0$			-2.0	mA
DC Current Gain	$h_{FE(1)}$	$V_{CE}=-4V$ $I_C=-1A$	1000			
	$h_{FE(2)}$	$V_{CE}=-4V$ $I_C=-2A$	500			
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C=-2A$ $I_B=-8mA$			-2.5	V
Base to Emitter On Voltage	$V_{BE(on)}$	$I_C=-2A$ $V_{CE}=-4V$			-2.8	V
Collector output capacitance	C_{ob}	$V_{CB}=-10V$ $I_E=0$ $f=0.1MHz$			200	pF

Electrical Characteristic Curve



/ Package Dimensions

mm TO-220 单位:




Dimensions in Millimeters			Dimensions in Millimeters				
Symbol	Min	Max	Symbol	Min	Max		
A	9.8	10.2	C	1.2	1.4		
R	3.56	3.64	B	6.3	6.7		
B1	9.0	9.4			15.7	16	
a	0.6	0.7	b1	0.6	0.7	h1	0.6
c1	0.4	0.6				h2	0.2
E	1.25	1.45					

TIP117

Rev. H Oct.-2018

/ Marking Instructions



Note:

BR: Company Code

TIP117: Product Type.

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-----|-----|----|---------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 255 | 5 | 5 | 0.5sec; | 2.Peak Temp.:255 5 , Duration:5 0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

270 5 10 1 sec. Temp.:270±5 Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type	Units					Dimension (unit mm ³)		
	Units/Bag /	Bags/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Bag	Inner Box	Outer Box
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

/ TUBE

Package Type	Units					Dimension (unit mm ³)		
	Units/Tube /	Tubes/Inner Box /	Units/Inner Box /	Inner Boxes/Outer Box /	Units/Outer Box /	Tube	Inner Box	Outer Box
TO-220/F	50	20	1,000	5	5,000	532×31.4×5.5	555×164×50	575×290×180

/ Notices